

SHERWOOD REGULATORS

www.SHERWOODvalve.com

SECTION A

SHERWOOD REGULATORS

First Stage Regulators



Used in two-stage systems with these second stage regulators shown below. Painted red for easy identification, this regulator has plenty of capacity for a 1000 gallon tank. A regulator with an integral relief valve protects against propane condensation in the first stage line and gives positive indication of regulator malfunction. This regulator has a 1/8" FNPT pressure port for monitoring outlet pressure. The inlet is at 12 o'clock and the vent outlet is at 6 o'clock.

CAPACITY BTU/HR	INLET CONNECTION	OUTLET CONNECTION	OUTLET SETTING	TYPE NUMBER	LIST PRICES
1,000,000	FPOL	3/4" FNPT	10 PSIG	800HPS3	51.16

Second Stage Regulators - Straight-thru type



Used in two-stage systems with the first stage regulator shown above. Sherwood's second stage regulators are colored green. They have the capacity to handle large loads and all are equipped with full capacity integral relief valves. The full capacity integral relief valve limits outlet pressure to a maximum of 2 psig, even with total regulator seat failure. They have a 1/8" FNPT pressure port for monitoring outlet pressure. The inlet and vent outlet are at 6 o'clock.

CAPACITY BTU/HR	INLET CONNECTION	OUTLET CONNECTION	OUTLET SETTING	TYPE NUMBER	LIST PRICES
500,000	1/2" FNPT	3/4" FNPT	11" wc	800JC	46.30
500,000	3/4" FNPT	3/4" FNPT	11" wc	800NC	40.60

Second Stage Regulator - Back-mount



Used in two-stage systems with the first stage regulator shown above. Sherwood's second stage regulators are colored green. They have the capacity to handle large loads and all are equipped with full capacity integral relief valves. The full capacity integral relief valve limits outlet pressure to a maximum of 2 psig, even with total regulator seat failure. They have a 1/8" FNPT pressure port for monitoring outlet pressure. The inlet and vent outlet are at 6 o'clock. The back-mount is the same as the straight-thru type, except that the outlet is at a right angle. This eliminates the need for a mounting bracket, making installation easier and faster.

CAPACITY BTU/HR	INLET CONNECTION	OUTLET CONNECTION	OUTLET SETTING	TYPE NUMBER	LIST PRICES
500,000	3/4" FNPT	3/4" FNPT	11" wc	800NBC	45.46

Integral Two-Stage Regulators



Combines first stage and second stage regulation into one unit. Ideal for use with installations of large cylinders (200, 300, 420 pounds) or stationary 500 and 1000 gallon tanks. The 920/921 Series regulator has a full capacity relief valve that limits outlet pressure to a maximum of 2 psig, even with total seat failure. It has a 1/8" FNPT port for monitoring outlet pressure.

CAPACITY BTU/HR	INLET CONNECTION	OUTLET CONNECTION	OUTLET SETTING	TYPE NUMBER	LIST PRICES
350,000	1/4" FNPT	1/2" FNPT	11" wc	920	64.10
350,000	1/4" FNPT	3/4" FNPT	11" wc	920A	64.10
350,000	FPOL	1/2" FNPT	11" wc	921	71.82
350,000	FPOL	3/4" FNPT	11" wc	921A	73.96