

## MISCELLANEOUS SHERWOOD VALVES and ADAPTERS

### Double Back Check Filler Valves




All valves are UL listed (per UL 125) and meet NFPA standards.

1855SD30

1855SD



1855SPD



1855SD90



623B

CONTAINER CONNECTION	LINE CONNECTION	FILL RATE at VARIOUS DIFFERENTIAL PRESSURES (GPM Propane)				TYPE NUMBER	LIST PRICES
		10	25	50	75		
3/4" NPT	1-3/4" Acme	19	30	43	60	1855SD	19.28
	1-3/4" Acme	19	30	43	60	1855SD30	30.82
	3/4" FNPT	19	30	43	60	1855SPD	29.32
	1/2" SAE Flare	19	30	43	60	1855SD90	27.68
1-1/4" NPT	1-3/4" Acme	70	92	144	158	623B	34.04

### Internal Spring Relief Valves for ASME Containers/Domestic Tanks



Used as a pressure relief device on ASME containers and domestic tanks up to 1,000 gallons capacity. Furnished with rain cap for protection against contamination.

INLET CONNECTION	START TO DISCHARGE SETTING	Flow Capacity SCFM Air		Tank Surface Area (Sq. Ft.)		TYPE NUMBER	LIST PRICES
		UL	ASME	UL	ASME		
3/4" NPT	250	1930	1709	79	68	433AM	31.28
3/4" NPT	275	—	1709	—	68	433AC	31.28
1" NPT	250	2755	2436	122	105	443AM	39.18
1" NPT	275	—	2436	—	105	443AC	39.18
1-1/4" NPT	250	4640	4406	230	216	453AM	58.68
1-1/4" NPT	275	—	4406	—	216	453AC	58.68

### Uni-Kap Relief Valve Covers



Uni-Kap fits virtually all popular relief valves and has these features: Meets NFPA requirements, fits over 100 different valves, replaces 25 different caps, reduces your inventory, and many others.

DESCRIPTION	TYPE NUMBER	LIST PRICES
Large (3/4" thru 1-1/4" valves)	UK85A	2.80
Small (1/2" and 3/4" valves)	UK85SM	2.80

### Vapor Return Valve



Has super positive backcheck valve. Attachment to the vapor hose coupling with its projecting nozzle opens the backcheck valve to permit flow in both directions.

INLET CONNECTION	OUTLET CONNECTION	TYPE NUMBER	LIST PRICES
3/4" NPT	1-1/4" ACME	1876	29.06

### Checkmate Liquid Withdrawal Excess Flow Valves for ASME Bulk Tanks



- UL listed (Conform to new requirements of UL 125)
- Improved gasket seal during connect and disconnect operations
- Accommodates permanent installation
- Valve body undercuts safety feature for accidental disconnect protection
- O-ring securely crimped in cap
- O-ring cap provides positive pressure and vacuum sealing
- Rated for high flow:
  - 5136 (22 GPM)
  - 5137 (34 GPM)
- Universal geometry: fits updated configuration
- Cap seals with minimum torque
- New union style adapter - fits all new UL listed valves



5136



5137



5138

DESCRIPTION	TYPE NUMBER	LIST PRICES
3/4" NPT Inlet x 1-5/8" - 12 UN Outlet	5136	30.60
1-1/4" NPT Inlet x 1-5/8" - 12 UN Outlet	5137	36.92
1-5/8" - 12 UN x 3/4" Adapter	5138	18.90

### Filler Hose Adapter



The 901B adapter is designed to be left in place on the filler hose.

INLET CONNECTION	OUTLET CONNECTION	TYPE NUMBER	LIST PRICES
1-3/4" ACME (male)	1-3/4" ACME (female)	901B	27.48

SECTION A MISCELLANEOUS SHERWOOD VALVES and ADAPTERS