

ASME TANKS and BOBTAIL DELIVERY TRUCKS

**SECTION N
ASME TANKS and BOBTAIL DELIVERY TRUCKS**

ASME Domestic Tanks



Ransome Tanks are built to the highest standards demanded by customers who want their investment to last with little or no maintenance.

Standard Features

- To increase longevity and assure surface preparation clean of all rust and mill scale, each tank is thoroughly shot blasted before repainting.
- After priming and applying a finish coat 3 mills thick, all tanks are cured under heat lamps to produce a protective coating that is not only attractive but so durable it will last for many years.
- Other features include extra heavy legs with anchoring holes that will not collapse under severe snow loads or if accidentally dropped.
- Forged steel lifting eyes that do not bend during moving or setting tanks.
- All tank fittings are neatly tucked under a well vented protective dome.



Fittings

- Filler Valve
- Service Valve
- Fixed Liquid Level Bleeder Valve
- Relief Valve
- Float Gauge
- Top Mounted Emergency Liquid Withdrawal
- Plugged Bottom Liquid Outlet on 325 gallon tanks and larger

Options

- Openings in addition to the standard
- Vapor Return Valve
- Internal Valves, Excess Flow Valves and other fittings as requested
- Stainless Steel Legs

TANK SIZE and DESCRIPTION	DIAMETER INCHES	OA HEIGHT INCHES	OA LENGTH INCHES	PART NUMBER	LIST PRICES
124 gallon ASME Domestic Tank	24	34	70	LP124	896.00
150 gallon ASME Domestic Tank	24	34	84	LP150	939.00
250 gallon ASME Domestic Tank	30	40	94	LP250	1146.00
325 gallon ASME Domestic Tank	30	40	119	LP325	1485.00
500 gallon ASME Domestic Tank	37	48	120	LP500	1640.00
1000 gallon ASME Domestic Tank	41	52	194	LP1000	3345.00
1250 gallon ASME Domestic Tank	41	52	221	LP1150	3410.00
1999 gallon ASME Domestic Tank	54	60	221	LP1999	11120.00

Bobtail Delivery Trucks

Standard Equipment

- Blackmer TLGLF3" flange pump
- Heavy Duty two-gear PTO
- Manual PTO, clutch and throttle
- Fisher C404-24 internal valve
- Blackmer 1-1/4" automatic bypass valve
- Neptune 1-1/2" ATC meter with 833 printing register
- 2" piping to the meter
- Hannay hose reel
- 100' of 1" LP Hose
- Hose end swivel
- Rego A7797 angle hose end valve
- Frame mounted toolbox
- RoughRid visible gauge
- Steel decking

Optional Equipment

- Air-controlled remote PTO, clutch and throttle
- Veeder-Root register
- Liquid control meter - 2"
- Midcom register and computer
- Aluminum register cover

Tank Sizes

- 2400 gallon capacity
- 2600 gallon capacity
- 2800 gallon capacity
- 3000 gallon capacity
- 3200 gallon capacity
- 3499 gallon capacity

Truck Chassis

- Kenworth
- Freightliner
- Chevrolet
- Ford
- International
- Propane
- Gasoline
- Diesel

Safety Equipment

- Safety Air operation
- Bettsexplosion-proof worklights
- All rear deck wiring in vapor-proof conduit
- (2) B: Crated fire extinguishers with brackets
- Road hazard kit
- First Aid kit
- Remote shutdown



P.O.A.